

GB Machinery



Brief Description

Oil hydraulic heavy duty mini-shear with single or three phase electric motor. Bronze bearings throughout.

Features

- Four sided reversible serrated blades.
- Tank mounted motor.
- Four way fork-lift entry base.
- Supplied ready to work.
- Foot pedal control – single or automatic stroke.
- Compact with parts accessible for easy service.
- Adjustable blade opening.
- Fully adjustable head guard.
- Adjustable head bearings
- Adjustable blades.

Deltax reserves the right to alter the product specification in any way without giving prior notification.

Specification	Dimension	DTX 680
Overall	Length	1534mm (60 $\frac{3}{8}$ ")
	Width	760mm (30")
	Height	1205mm (47 $\frac{1}{2}$ ")
	Weight	500kg / 1100 lbs
Blade	Length	680mm (26 $\frac{3}{4}$ ")
	Opening	50 – 298mm (2" - 11 $\frac{3}{4}$ ")
Blade Table	Height	794mm (31 $\frac{1}{4}$ ")
Max Shear Force	Ton Force	55
Shear Capacity	Steel Round Bar 45 kg/mm	30 (1 $\frac{3}{16}$ ")
Oil	ISO 46	135ltr (30 Gall)
Horsepower	Single Phase	3HP (2.2kW)
	Three Phase	5.5HP (4kW)
Speed	Single Phase	7 $\frac{1}{2}$ - 30 cuts/min
	Three Phase	15 - 60 cuts/min